

# FT-18XHKH200S

## Camera

---

Image Sensor: | 2MP Progressive Scan CMOS

---

Effective Pixels: | 1920(H)x1080(V)

---

Signal System: | PAL/NTSC

---

White Balance: | Auto

---

AGC: | Auto/Manual

---

BLC: | Support

---

Focal Length: | 5-90MM, 18X

---

Signal Transfer: | AHD/CVI/TVI/CVBS Selectable

---

## Pan & Tilt

---

Rotation Range: | Pan: 360°, Vertical 90°, Auto Flip 180

---

Rotation Speed: | Manual speed 80°/s

---

Preset Points: | 256pcs preset( Dwell time 01-60s interval available)

---

Guard Tours: | 4 groups ( Each group 16 preset, dwell time and speed selectable)

---

AB scan range: | Any point in Pan range: 0°~360°

---

AB scan speed: | 1-9 grades

---

## Infrared

---

IR irradiation distance: | 150m

---

LEDs: | 8Pcs laser LED

---

Support Ambient Light  
Detection: | IR illumination on 1-9 Grads selectable

---

## General

---

RS-485 Protocols: | Pelco-P, Pelco-D

---

Menu Language: | English

---

Power Supply: | 12V DC

---

Power Consumption: |  $\leq 10W$

---

Lightning Protection: | Transient voltage 6000V

---

Working Temperature/H  
umidity: |  $-15^{\circ}C \sim +60^{\circ}C$

---

Dimensions: | 30 \*30 \*42 cm

---

Weight (approx.): | 10KG

---